

ENERGY FOR YOU...



SK-038 42 Příbovce 343
Tel.: +421/43/42 94 466
Tel.: +421/43/42 94 916
Fax.: +421/43/42 94 026
E-mail: tts@tts-martin.sk
www.tts-martin.sk



Diesel engine LOMBARDINI

Base power range from 15,8kVA within 43,7kVA

Nominal speed / frequency: 3000min⁻¹ / 50Hz

Nominal voltage : 3x230V / 400V



GENSET TYPE	STAND-BY POWER (LTP) (kVA / kW)	PRIME POWER (PRP) (kVA / kW)	ENGINE TYPE	INDUCTION	SPEED REGULATION	FUEL CONSUMPTION (PRP) (L/h)	FUEL TANK VOLUME (L)	BASE UNIT DIMENSIONS (L / W / H) (mm)	BASE UNIT WEIGHT (kg)	CANOPY TYPE	WEIGHT 100LWA (kg)	WEIGHT 90LWA (kg)
MP13 B	17,4 / 13,9	15,8 / 12,6	LDW 1003 FOCS	N	M	4,6	50	1400/700/950	250	A	550	600
MP20 B	26,2 / 21	28,8 / 23	LDW 1603 CHD	N	M	8,1	50	1400/700/1000	340	A	640	690
MP27 B	37,8 / 30,2	34,4 / 27,5	LDW 2204 CHD	N	M	8,4	100	1400/700/1000	450	B	800	850
MP38 B	48 / 38,4	43,7 / 35,0	LDW 2204T CHD	T	M	12,3	100	1400/700/1000	465	B	815	865

Induction

- N - natural
- T - turbocharged
- TA – turbocharged with intercooler

Option:

- version for dusty condition

Speed regulation

- M – mechanical (4%)
- E – electronic (0,25%)

Canopy type (mm) (L / W / H)

- A – 2000mm / 800mm / 1140mm
- B – 2400mm / 800mm / 1140mm

Option:

- genset in container
- retention bath for genset without canopy
- industrial exhaust silencer
- residential exhaust silencer
- fast trailer
- remote genset monitoring and control
- engine heater
- increased generator protection level IP45