

Work light

CODICE/ITEM/CODE	IS460	IS404	IS407
	 	 	 
Batteria / Battery / Batterie	3 x AAA/LR03 (not included)	3 x AA/LR6 (not included)	3 x AA/LR6 (not included)
Tecnologia della Luce / Light technology / Technologie de la lumière	24 LED	8 LED SMD + 1 High power 0,5 W	3W COB LED + 6 LED standard
Potenza (W) / (W) Power / Puissance (W)			3W
Portata / Range / Distance d'éclairage	20 mt	15 mt	10 mt
Lumen / Lumen / Lumen	12 Lm	8 LED SMD : 220 1 High power 0,5 W : 30 Lm	3W COB LED: 200 Lm 6 LED: 25 Lm
Autonomia / Runtime / Autonomie	16 ore/hrs	>40 ore/hrs	HI: 20 ore/hrs LOW: 57 ore/hrs
Tipo di luce / Kelvin degrees / Degrés Kelvin	6000K	6000K	6000K
Fascio di luce / Light beam / Type de faisceau	Diffuse Light	Diffuse / Focus Light	Diffuse / Focus Light
Durata di vita del LED / LED Life time / Durée de vie des LED	30.000 ore/hrs	30.000 ore/hrs	30.000 ore/hrs
Dimensioni prodotto / Product dimensions / Dimensions	210 x 60 x 25 mm	60 x 50 x 230 mm	220 x 59 x 36 mm
Materiale / Material / Matériau	Rubber / ABS	ABS	ABS + PS
Grado di protezione / Protection degré / Degré de protection	IP20	IP20	IP20
Accessori / Accessories / Accessoires	Gancio/Hook Calamita/Magnet	Gancio/Hook Calamita/Magnet	Gancio/Hook Calamita/Magnet
Peso netto / Net Weight / Poids net	64 g	240 g	115 g

IS460



PACKING	INNER	MASTER
 / 	 pcs	 pcs
Display 12 pcs	12	24

IS404



PACKING	INNER	MASTER
 / 	 pcs	 pcs
Blister F5	6	48

IS407



PACKING	INNER	MASTER
 / 	 pcs	 pcs
Blister F5	6	48

Work light ricaricabili

CODICE/ITEM/CODE	IS475	IS575	IS408RST	IS142R	IS147R	IR50RST
						
Alimentazione / Power supply / Alimentation	230V ~ 50Hz / 5V === 1A	230V ~ 50 Hz / 5V === 1000mA	230V ~ 50 -Hz / 6V === 300mA	220/240V ~ 50 Hz / 8,5V === 1,5A	220/240V ~ 50 Hz / 12,6V === 1,5A	220V ~ 50Hz / 12V === 2,3A
Batteria / Battery / Batterie	Li-ion 3,7V 2200mAh (18650) included	3,7, 2200 mA Li-ion	3,7V 1500mA Lithium battery	7,4V 4,4Ah, Li-ion	11,1V 4400mAh, Lithium	Li-ion 7,4V 13,2Ah
Tecnologia della Luce / Light technology / Technologie de la lumière	3W SMD LED (6 pcs)	3W COB	6 LED SMD 5730 (main-body 3W) 1 LED SMD 3030 (flashlight 1W)	10W LED SMD	20W LED SMD	COB LED
Potenza (W) / (W) Power / Puissance (W)	3W	3W	3W + 1W	10W	20W	50W
Portata / Range / Distance d'éclairage	N/S	5 mt	18 mt (6LED - main body) 40 mt (1LED - flashlight)	N/S	N/S	N/S
Lumen / Lumen / Lumen	300 Lm	240 Lm	220 Lm (6LED - main body) 90 Lm (1LED - flashlight)	700 Lm	1200 Lm	3800 Lm
Tempo di ricarica / Charging Time / Temps de recharge	4 ore/hrs	4 ore/hrs	5 ore/hrs	4-5 ore/hrs	6 ore/hrs	5 ore/hrs
Autonomia / Runtime / Autonomie	8 ore/hrs (50%) 4 ore/hrs (100%)	3,5 ore	5 ore/hrs (6LED - main body) 7 ore/hrs (1LED - flashlight)	3 ore/hrs	3 ore/hrs	Hi: 6 ore/hrs Low: 15 ore/hrs
Tipo di luce / Kelvin degrees / Degrés Kelvin	6000K	6000K	6000K	6000 K	6000 K	6500K
Fascio di luce / Light beam / Type de faisceau	Diffuse light	Diffuse light	Luce precisa / Focus light Luce diffusa / Diffuse light : 120°	diffusa 110°	diffusa 120°	Diffuso / Diffuse 105°
Durata di vita del LED / LED Life time / Durée de vie des LED	30.000 ore/hrs	30.000 ore/hrs	30.000 ore/hrs	30.000 ore/hrs	30.000 ore/hrs	30.000 ore / hours
Dimensioni prodotto / Product dimensions / Dimensions	Lampada: 58x40x240 mm Lampada + base: 70 x 100 x 265 mm	57 x 50 x 410 mm	19 x 5,9 x 4 cm (normal) 29,5 x 5,9 x 4 cm (pull-out)	167 x 183 x 240 mm	220 x 185 x 195 mm	260 x 110 x 275 mm
Materiale / Material / Matériau	ABS	ABS	ABS + PC	Alluminio/Aluminium	Alluminio/Aluminium	AL+PC
Grado di protezione / Protection degré / Degré de protection	IP20	IP20	IP22 - IK5	IP54	IP65	IP54
Accessori / Accessories / Accessoires	Supporto di carica / Charging base Adattatore 220V / 220V adaptor Adattatore 12V / 12V adaptor Magnete - Gancio / Magnet - Hook	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor Magnete / Magnet	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor Power bank Indicatore di carica / Charge indicator	Adattatore 12V / 12V Car adaptor Trasformatore 220V / 220V Home adaptor Powerbank Bluetooth speaker Indicatore di carica / Charge indicator
Peso netto / Net Weight / Poids net	360 g	230 g	422 g	985 g	1400 g	2150 g

IS475



PACKING	INNER	MASTER
	pcs	pcs
Blister F5	6	24

IS575



PACKING	INNER	MASTER
	pcs	pcs
Blister F5	6	24

IS408



PACKING	INNER	MASTER
	pcs	pcs
Blister F5	6	24

IS142R



PACKING	INNER	MASTER
	pcs	pcs
Colour box	-	6

IS147R



PACKING	INNER	MASTER
	pcs	pcs
Colour box	-	4

IR50RST



PACKING	INNER	MASTER
	pcs	pcs
Colour box	1	4