



PERSONAL
COMPUTERS



SMALL
COMPUTERS
NETWORK

iDialog / iDialog Plus

400-800 VA / 400-1600 VA
single-phase

iDialog / iDialog Plus 400-800 VA / 400-1600 VA



The **iDialog** UPS has been designed to protect PCs and critical peripherals in home and small office environments. iDialog is easy to install and provides powerful, economic protection for:


- IT equipment including PCs, Media Centers, PoE, VoIP and other such peripherals
- TVs, Home Cinemas, Satellite and Digital Terrestrial receivers, DVD readers and writers
- Modems and xDSL routers
- Small household appliances

Particolare dei display



CHARACTERISTICS

- Maximum power protection with **PowerShield³** UPS monitoring and shutdown software available for free download from our website www.riello-ups.com
- Suitable for installation on PC's running Windows Vista, 2003, XP, 2000, Me, 98; Linux, Mac OSX and the Sun Solaris operating system.
- Compact dimensions and ergonomic design: **iDialog** can be placed on a desk top or other convenient location, with easy to access connections and informative front panel.
- Front panel LCD display (**Plus** version only) providing status, load and battery information and LEDs (standard version).
 - Silent running: **iDialog** can be used to protect other sensitive electronic devices including Home Cinemas, CD Writers, DVD players, Satellite and Digital Terrestrial receivers.



2 YEAR WARRANTY

MODELS	ID 40	ID 60	ID 80	IDP 40	IDP 60	IDP 80	IDP 110	IDP 160	
POWER	400VA/240W	600VA/360W	800VA/480W	400VA/240W	600VA/360W	800VA/480W	1100VA/660W	1600VA/960W	
INPUT									
Rated voltage	220-240 Vac								
Voltage range	230 Vac (+20/-25%)								
Frequency	50/60 Hz auto sensing								
OUTPUT									
Voltage on mains operation	230 Vac (+/- 15%)								
Voltage on battery operation	230 Vac (+/- 10%)								
Frequency on battery operation	50 or 60 Hz (+/- 1%)								
BATTERIES									
Type	VRLA AGM Maintenance-free lead-acid								
Recharge time	6-8 h								
ENVIRONMENTAL									
Weight (kg)	3			3.2		3.4	6.6	7	
Dimensions (hwd) (mm)	192 x 90 x 232						275 x 97x 315		
Tel/Modem protection	RJ11/45 connectors								
Communication	n.d.			USB					
Output sockets	4 IEC		4 IEC or 3 Schuko/Italian or 3 french			6 IEC or 4 Schuko/Italian or 4 french			
Safety compliance	EN 62040-1-1 and Directives 73/23 EC, 93/68 EC, EN 62040-3								
EMC conformance	EN 62040-2 and Directives 2004/108 EC, 93/68 EC								
Marks	CE								
Operating temperature	0°C / +40°C								
Colour	Dark grey								
Altitude and relative humidity	6000 meters max. elevation, < 95% non condensing								
Accessories provided	2 output supply cables (IEC version), 1 USB cable (plus version), user guide								

